

Maniglioni tipo HFR

Shackles type HFR

Asas tipo HFR

Dimensioni Dimensions Dimensiones mm											Carico minimo di rottura Minimum breaking force Carga mínima de rotura kN	Massa Mass masa kg ?	Relativi tralci di catena per ruote Corresponding chain strands for wheels Tramos de cadenas correspondientes para ruedas	
t	d ₁	d ₂	d ₃	d ₄	h ₁	h	b	w	s	L	3HS	kg ?	lisce smooth lisas DIN 764/766 d mm	dentate toothed dentadas DIN 764 d mm
45	13	15	5	M12	33	58	30	75	12	28	110	0.60	10	13
56	16	18	5	M14	41	70	45	95	15	32	165	0.80	13	16
63	18	21	5	M16	43	77	50	110	15	40	220	1.10	16	18
70	20	23	5	M20	48	86	55	120	15	54	280	1.60	18	20
80	23	26	5	M20	53	95	60	130	20	54	360	1.90	20	23
91	26	29	6	M24	60	107	70	155	20	58	450	2.90	23	26
105	30	34	6	M24	68	122	80	165	20	58	630	4.10	26	30
126	36	40	8	M30	81	144	85	200	25	68	860	6.40	30	36
147	42	46	8	M36	93	169	95	230	25	68	1160	9.50	36	42

